

ABS Series

Guardian Audio® ABS Series active speakers have a speakon output jack to connect and power a passive speaker. Pair an ABS10A, ABS12A or ABS15A active speaker with an ABS10, ABS12, or ABS15 passive speaker. The ABS10A also has a microphone input and can be used as a stand alone portable system.

Active Model	Woofers	HF Driver	Power @ 8Ω / 4Ω	Sensitivity	Frequency Response
ABS10A	10" Cast Frame	1.375"	150 / 250	98dB (1w/1m)	50Hz~20kHz
ABS12A	12" Cast Frame	1.375"	250 / 450	98dB (1w/1m)	45Hz~20kHz
ABS15A	15" Cast Frame	1.375"	250 / 450	99dB (1w/1m)	45Hz~20kHz

Passive Model	Woofers	HF Driver	RMS Power	Sensitivity	Frequency Response
ABS10	10" Cast Frame	1.375"	200 Watts	98dB (1w/1m)	50Hz~20kHz
ABS12	12" Cast Frame	1.375"	250 Watts	98dB (1w/1m)	45Hz~20kHz
ABS15	15" Cast Frame	1.375"	300 Watts	99dB (1w/1m)	45Hz~20kHz

The ABS Series speakers use cast frame woofers and titanium diaphragm compression drivers. The internal crossover incorporates a lamp fuse for superior speaker protection. There are embedded M8 fly points for installing and a 1 3/8" stand mount to serve as main front of house system. One side of the cabinet is angled for use as a floor monitor.



ABS12A
ABS15A

ABS10A



ABS10
ABS12
ABS15

